



Neste Gear UTTO

Hydraulic and driveline oil for agricultural equipment

PERFORMANCE CLAIMS API GL-4

Allison C3, C4
 Case MAT 3505
 Ford M2C-134 A/B/C/D, M2C-86B/C
 Ford/New Holland FNHA-2-C-200.00 (hydraulic oil 134)
 Ford/New Holland FNHA-2-C-201.00 (M2C-134D)
 John Deere J20 A/B/C, J14B/C, J21A
 Komatsu
 Kubota UDT
 Massey Ferguson M1135, M1141, M1143, M1145
 Steiger SEMS 17001
 Versatile 23M, 24M
 Volvo 97303 (VCE WB 101)
 White Farm (AGCO) Q-186
 ZF TE-ML 03E, 05F, 06D, 06K, 06N, 06R, 17E, 21F

DESCRIPTION

Neste Gear UTTO is a combined gear and hydraulic oil for tractors, with the friction properties required for wet brakes. Its wear resistance exceeds that of ordinary gear/hydraulic oils. Neste Gear UTTO also offers good oxidation and corrosion resistance.

SPECIAL FEATURES AND BENEFITS

- Good EP properties
- Multipurpose lubricant
- Very good wear protection

TYPICAL CHARACTERISTICS

Density kg/m ³ 15°C	876
Flash Point °C (COC)	238
Pour Point °C	-42
Viscosity index	133
Viscosity cSt/ 40 °C	67
Viscosity cSt/ 100 °C	10
SAE equivalence	10W-30

APPLICATIONS

Neste Gear UTTO oil is used in tractor gears, rear axles, hydraulics and wet brakes. Its viscosity is standard, and it is suitable for year-round use with the exception of severe below-zero colds.