



## Neste Pro Axle 75W-140

Fully synthetic drive and differential gear oil

### PERFORMANCE CLAIMS

SAE 75W-140

API GL-5

MIL-L-2105 D

Scania STO 1:0

### DESCRIPTION

Neste Pro Axle 75W-140 is made of a fully synthetic base oil mixed with extreme pressure, oxidation and rust resistance additives. Good operation properties at severe below-zero temperatures and low friction drag, which make for good fuel economy, are special features of this oil.

### SPECIAL FEATURES AND BENEFITS

- Extra wide operating temperature area
- Excellent EP properties
- Low friction
- Good oxidation stability

---

### TYPICAL CHARACTERISTICS

Density kg/m <sup>3</sup> 15°C	857
Flash Point °C (COC)	220
Pour Point °C	-48
Viscosity index	181
Viscosity cSt/ 40 °C	172
Viscosity cSt/ 100 °C	25
Viscosity cP/ °C	111000 / -40
Tunnelling point °C	<-45

---

### APPLICATIONS

Neste Pro Axle 75W-140 is for heavy-duty transportation - year-round use. It can be blended with ordinary gear oils if necessary and it does not damage the gaskets.

Neste Pro Axle 75W-140 fills Scania STO:1 requirements and is suitable for Scania drive gears especially in cold climate conditions.

---