



Neste Pro F 5W-30

Synthetic motor oil

PERFORMANCE CLAIMS

SAE 5W-30

API SL, SJ/CF

ACEA A5/B5, A1/B1

Ford WSS-M2C912-A1

Ford WSS-M2C913-A, B, C, D

Renault 0700

Recommended for use where Fiat 9.55535.G1 is specified.

DESCRIPTION

Neste Pro F 5W-30 is a synthetic motor oil which is intended for use in new low friction and clean burning gasoline engines.

SPECIAL FEATURES AND BENEFITS

- Excellent cold start performance
- Improved fuel economy benefits
- Long drain interval

TYPICAL CHARACTERISTICS

| | |
|--------------------------------|------------|
| Density kg/m ³ 15°C | 853 |
| Flash Point °C (COC) | 222 |
| Pour Point °C | -45 |
| Viscosity index | 166 |
| Viscosity cSt/ 40 °C | 55 |
| Viscosity cSt/ 100 °C | 9.8 |
| Viscosity cP/ °C | 4200 / -30 |

APPLICATIONS

Neste Pro F 5W-30 is specially suitable for new Ford engines where Ford WSS-M2C913-C engine oil is required. It is also backwards compatible when Ford WSS-M2C913-B, M2C913-A or M2C912-A1 quality oil is specified.

Neste Pro F 5W-30 is recommended for those gasoline and diesel motors which are designed for low friction and low viscosity oil. Suitable especially for Hyundai and KIA. Also for LPG motors.
