



Neste Pro+ W LL-III 5W-30

Fully synthetic motor oil

PERFORMANCE CLAIMS

SAE 5W-30

ACEA C3

BMW Longlife-04

MB-Approval 229.51

VW 504.00, VW 507.00

DESCRIPTION

Neste Pro+ W LL-III 5W-30 is especially developed for the LongLife Service used in VW, Audi, Skoda and Seat diesel and gasoline engines with extended oil drain intervals.

SPECIAL FEATURES AND BENEFITS

- Excellent cold start performance
- Improved fuel economy benefits
- Long drain interval
- Low emission

TYPICAL CHARACTERISTICS

	5W-30
Density kg/m ³ 15°C	853
Flash Point °C (COC)	230
Pour Point °C	-42
Viscosity index	170
Viscosity cSt/ 40 °C	69
Viscosity cSt/ 100 °C	11.8
Viscosity cP/ °C	5800 / -30

APPLICATIONS

Suitable for engines with DPF (Diesel Particulate Filter) emission aftertreatment system which requires low/mid SAPS (Sulphated Ash, Phosphorus and Sulphur) oil. In these diesel engines engine oil requirement is VW 507.00. In gasoline engines requirement is VW 504.00.

Neste Pro+ W LL-III 5W-30 is suitable for most VAG group LongLife Service cars which require VW 503.00 or 506.00 type of engine oil.

Older than -98 year models diesel engines with pump injector technology and normal 15 000 km oil drain intervals Neste Premium+ 5W-40 (VW 505.01) engine oil can be used.

Extended oil drain intervals may be applied as indicated by the car manufacturer.

When using extended oil drain intervals use Neste Pro+ W LL-III 5W-30 as a top up oil.