



Product Data Sheet

MOTOR OIL SL 10W-50

Product Description:

MOTOR OIL SL 10W-50 is an universal performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

MOTOR OIL SL 10W-50 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Good thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SL 10W-50 exceeds the following performance criteria:

MB 229.1

ACEA A3/B4

API SL/CF

VW 505.00

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	10W-50
Density@15°C	kg/m ³	ASTM D4052	871
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	135
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	17.0
Viscosity Index		ASTM D2270	155
Viscosity CCS @-25°C, max	cP	ASTM D2270	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.9
Sulphated Ash	%Wt	ASTM D874	0.95

Product Nr: 4207

Date Issued: 10-09-2012

Date Superseded: 21-03-2011

Revision nr: 1