



Product Data Sheet

MOTOR OIL SF 15W-40

Product Description:

MOTOR OIL SF 15W-40 is a multi functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger car and light vans with or without turbo compressor. MOTOR OIL SF 15W-40 is not suited for engines equipped with a Diesel Particle Filter (DPF).

MOTOR OIL SF 15W-40 is formulated with special selected base stocks in combination with unique additive package to reach the following properties:

- Stable viscosity index.
- Good protection against rust, corrosion and wear.
- Good dispergency and detergency properties.
- Good antifoam properties.

MOTOR OIL SF 15W-40 exceeds the following performance criteria:

API SF/CD

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density@15°C	kg/m ³	ASTM D4052	879
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	107
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	135
Viscosity CCS @-20°C, max	cP	ASTM D2270	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	5.2
Sulphated Ash	%Wt	ASTM D874	0.66

Product Nr: 4212

Date Issued: 16-03-2015

Date Superseded: 27-06-2010

Revision nr: 1