



Product Data Sheet:

MOTORCYCLE OIL SYN 2T

Product Description:

MOTORCYCLE OIL SYN 2T is a fully synthetic lubricant developed for air & water cooled 2-stroke engines. **MOTORCYCLE OIL SYN 2T's** special formulation ensures excellent engine protection, cleanliness and low smoke even under extreme operating conditions.

MOTORCYCLE OIL SYN 2T offers very good lubricity against piston scuffing and wear of engine components. The advanced formulation provides exceptional control against engine deposits, exhaust system blocking and extended engine life without power loss, and reduces visible exhaust smoke. Low ash additive technology prevents pre-ignition and spark plug and easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

MOTORCYCLE OIL SYN 2T is recommended for high-powered 2-stroke motorcycles/scooters operating under different conditions.

MOTORCYCLE OIL SYN 2T is suitable for oil-injection and premix lubrication systems; always follow manufacturer's recommendations for oil-fuel ratio.

MOTORCYCLE OIL SYN 2T is also suitable for 2-stroke engines in all terrain vehicles, snow mobiles, lawn mowers and other applications requiring oils of this quality.

Specifications:

Exceeds: API TC, ISO-L-EGD, JASO FD

Property:	Test Method:	Typical Values:
Density @ 15°C	ASTM D4052	878 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	68 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	11 mm ² /s
Viscosity Index	ASTM D2270	150
Flash Point	ASTM D92	>90°C
Pour Point	ASTM D97	-45°C
Total Base Number	ASTM D2896	1.6 mgKOH/g
Sulphated Ash	ASTM D874	0.13 wt %

Product nr: 4295

Date Issued: 08/08/2011

Date Superseded: 07/07/2010

Revision nr: 01