



Product Data Sheet:

AUTOGEAR OIL SYN 75W-90

Product Description:

AUTOGEAR OIL SYN 75W-90 is a fully synthetic supreme performance total driveline gear lubricant designed to meet the requirements of European drive trains of light and heavy duty commercial vehicles.

AUTOGEAR OIL SYN 75W-90 is formulated from carefully selected synthetic base stocks and an advanced technology additive system. **AUTOGEAR OIL SYN 75W-90** gives unmatched protection towards gear components regarding wear and scoring. Furthermore **AUTOGEAR OIL SYN 75W-90** provides very good anti-corrosion protection and has been carefully inhibited against the formation of foam.

The high viscosity index of **AUTOGEAR OIL SYN 75W-90** improves “shift ability”, especially at lower temperatures and reduces wear during warming-up periods. The exceptional shear stability guarantees a long lasting oil film strength and the viscometric of the oil enables improved fuel economy.

AUTOGEAR OIL SYN 75W-90 is recommended for European drive trains requiring oils meeting MAN M 3343 Type S (Formerly MAN M 3343 Type SL). Furthermore **AUTOGEAR OIL SYN 75W-90** is recommended in manual transmissions and axel drives requiring GL-4/GL-5 and MT-1 performance.

Specifications:

Exceeds: API GL-4/GL-5/MT-1, MAN 3343 Type M, MAN 341 Type E-2, SAE J2360, MIL-L-PRF-2105E, Scania STO 1:0, Mack GO-J, DAF, IVECO, MB 235.0, ARVIN MERITOR 0-76-N, Renault B0032/2 annex 3, ZF TE-ML 02B/05A/7A/08/12E/16B/C/D/ 17B/19B/21A

Property:	Test Method:	Typical Values:
SAE Viscosity Grade	SAE J306	75W-90
Density @ 15°C	ASTM D4052	876 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	102 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	15.2 mm ² /s
Low-Temperature Brookfield Viscosity @ -40°C	ASTM D2983	<150000 cP
Viscosity Index	ASTM D2270	140
Flash Point	ASTM D92	190°C
Pour Point	ASTM D97	-36°C

Product nr: 4310

Date Issued: 08/08/2011

Date Superseded: 26/07/2010

Revision nr: 02